

# Everon® Copper Datacom E250 Unshielded OCK6UV, E250U Jack, RJ45 Vol, Cat6, BP480, White

CORNING

**Part Number:**  
**FQ100031241**

Our Cat.6 copper interconnect products work together to provide an easy-to-use solution for deploying high-speed connections throughout a building. The RJ45 jack is a key component in this system. The jack's unique two cable entry points help make installation simple. The traditional one-click design enables an easy, tool-less termination on unshielded twisted pair cables, meeting industry performance standards.

## Features and Benefits

### Tool-less jack

Easy and quick to install - reliable connection  
The conductors are wired in a single operation

### Two cable entry points

Less cable bending required - better compliance with minimum bend radius  
Enables a wide range of cable routing options  
Easy to use in tight spaces

### Reusable

Jack can be reused even after wiring mistake

### No untwisting of pairs before termination

Minimized stripping length - limited pair untwist - pairs kept together, no wire guide required

### Clip-in mounting

Designed to fit many other accessories


### Accepts solid and stranded conductors

Enables "jack-to-plug" cables to be manufactured using stranded conductors

### Integral shutter

No additional shuttering required on faceplates

### PoE Applications



Everon® Copper Datacom E250 Jack, OCK6UV, E250U, RJ45 Vol, Cat6, BP480, White

# Everon® Copper Datacom E250 Unshielded OCK6UV, E250U Jack, RJ45 Vol, Cat6, BP480, White



## Specifications

### General Specifications

Category	6
----------	---

### Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	ISO/ IEC 11801 Edition 2. Arm 1-2, EN 50173-1 : 2011, ANSI/ TIA/ EIA-568-C.2-2009, ISO 60512-99-01
Design And Test Criteria	IEEE 802.3 1GBASE-T, IEEE 802.3at

### Design

Jack Type	RJ45 - 8/8
Housing material	Plastic
Colour	White
Insulation diameter max.	1.6 mm
Conductor	AWG 26 - 22
Number of Stranded Wires	7

### Mechanical Specifications

Contact surface	Gold, 1.6 µm
Reproducibility	Several times reusable
Solid Wire Diameter	5 mm to 65 mm

### Electrical Specifications

Lead Through Resistance	< 200 mΩ
Insulation resistance	> 500 MΩ
Voltage Rating (Maximum)	<75

# Everon® Copper Datacom E250 Unshielded OCK6UV, E250U Jack, RJ45 Vol, Cat6, BP480, White



Dimensions	
Height	23 mm
Width	18 mm
Depth	34 mm

Ordering Information	
Product Number	FQ100031241
Packaging method	Bulk / 1 big Box
Shipping weight	69 kg
Units per delivery	480/1



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany  
+00 800 2675 4641 • FAX: • [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2026 Corning Optical Communications. All rights reserved.