

Everon® Copper Datacom U/UTP 450/23, Category 6, LSZH™/FRNC, Dca 4P, Grey



Part Number:
XE004239879

The Everon® Copper Datacom U/UTP 450/23 cable is designed up to 450MHz and its transmission characteristics exceed Category 6 specifications according to EN50288-6-1 IEC 61156-5. High system margins for the complete link according to the last version of ISO/IEC 11801 and EN 50173 (Series) will be achieved by using corresponding hardware together with this highend copper cable. The cable has a streamlined construction and low weight. Unshielded cable (U/UTP).

Features and Benefits

U/UTP 450/23 cable designed up to 450 MHz

Fulfils all requirements of category 6 EN50288-6-1 and IEC 61156-5

Suitable for Classe D to E according to ISO/IEC 11801. EN50173 and 10 Gigabit Ethernet according to IEEE 802.3an

Tested and approved for Power over Ethernet applications (PoE/PoE+/4PPoE) according to IEEE 802.3af, IEEE 802.3at and IEEE 802.3bt up to 90W

Certified by a vendor-independent and impartial test lab

Low smoke and halogen-free (LSZH)

Unshielded cable (U/UTP)

Length marking on jacket

Dca -s2, d2, a1

Everon® Copper Datacom U/UTP 450/23, Category 6, LSZH™/FRNC, Dca 4P, Grey

CORNING

Specifications

General Specifications	
Category	6
Cable type	U/UTP
Halogen-free	Yes
Construction	Simplex, 4P
Reaction to Fire	Dca-s2, d2, a1
Legacy Part Number	VOL6UL4305
Brand	Everon®

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	IEC 61156-5, EN 50288-6-1, ISO/IEC 11801 Ed. 2.2, EN 50173-1, ANSI/TIA-568-C.2, IEC 60304
Design And Test Criteria	Tested and approved for Power over Ethernet applications (PoE/PoE+/4PPoE) according to IEEE 802.3af, IEEE 802.3at and IEEE 802.3bt up to 90W
Flame propagation test	IEC 60332-1
Smoke density	IEC 61034-2
Halogen content test	Zero Halogen to IEC 60754-1
Level of corrosion	Non-corrosive according to IEC 60754-2

Environmental Conditions	
Temperature range, installation	0 °C to 50 °C
Temperature range, operation	-20 °C to 60 °C

Cable Design	
Conductor	Copper Wire, AWG 23/1
Conductor insulation	Solid PE

Everon® Copper Datacom U/UTP 450/23, Category 6, LSZH™/FRNC, Dca 4P, Grey

CORNING

Cable Design

Twisting	2 cores to a pair
Outer jacket material	LSZH/FRNC
Outer jacket colour	Grey

Mechanical Characteristics

Fire load	602 MJ/km
Nominal outer diameter	5.9 mm
Min. bend radius installation	8x Cable-Ø
Maximum tensile strength	100 N

Electrical Characteristics

Conductor resistance unbalance	2 %
Delay skew	40 ns/100 m
Max. loop resistance	190 Ω/km
Propagation delay	520 ns/100 m
Voltage rating	Less than 75 V DC max and less than 50 V ACC max
Propagation velocity at >10 MHz (NVP*c)	67 %
Coupling attenuation	40 dB
Insulation Resistance	> 5000 MΩ*km

Ordering Information

Product Number	XE004239879
Cable length	305 m
Packaging method	Drum
Units per delivery	1/1

Everon® Copper Datacom U/UTP 450/23, Category 6, LSZH™/FRNC, Dca 4P, Grey

CORNING



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
00 800 2676 4641 • FAX: • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2026 Corning Optical Communications. All rights reserved.