

# Closet Connector Housing (CCH) Three rack units, holds six CCH connector panels

CORNING

## Part Number: CCH-03U

Closet connector housings (CCHs) provide interconnect or cross-connect capabilities between outside plant, riser or distribution cables and opto-electronics. Like other LANscape solutions hardware, the housings accept CCH connector panels. In addition, the housings accept CCH cassettes and CCH modules.

From fiber and cable routing and strain relief, to port labeling and termination, these housings reduce the risk of error that can disrupt networks. The units are designed for rack mounting in 19-in (48 cm) racks or optional 23-in (58 cm) equipment racks (1.75-in EIA hole spacing). They are available in rack space options of 1U (two panels, cassettes or modules), 2U (four panels, cassettes or modules), 3U (six panels, cassettes or modules) and 4U (12 panels, cassettes or modules). The 1U, 2U and 3U options feature a slide-out tray and see-through, removable top covers. The CCH-04U features a clear door, removable front and rear enclosures and a platinum-colored interior for maximum visibility and access.

Every CCH housing is shipped complete with strain relief brackets, routing clips and guides, and mounting brackets for proper installation. Documentation labels are provided and components can be added as needed to construct a fiber distribution frame for any application. All housings include a removable tinted polycarbonate front door.

## Features and Benefits

### **Durable, polycarbonate-tinted front door for viewing jumpers**

Ideal for pigtail splicing

### **Removable, translucent top covers (1U, 2U, 3U), rear cover (4U)**

Visibility and ease of access for installation, testing, and troubleshooting

### **Internal and external strain-relief options**

Flexibility for installation and moves, adds, and changes (MACs)

### **Accepts panels, modules, and cassettes**

Variety of field-termination options

### **Adaptable to use as a modular splice housing**

Splices are stored and protected in same footprint



Closet Connector Housing (CCH), three rack units, holds six CCH connector panels

# Closet Connector Housing (CCH) Three rack units, holds six CCH connector panels

CORNING

## Specifications

### General Specifications

|               |                                                    |
|---------------|----------------------------------------------------|
| Product Type  | Housings                                           |
| Environment   | Indoor                                             |
| Access Type   | Front and rear access slidable                     |
| Mounting Type | Rack-mount, Cabinet-mount                          |
| Application   | Carrier Networks, Data Center, Enterprise Networks |

### Standards

|                        |                                                                                                                              |
|------------------------|------------------------------------------------------------------------------------------------------------------------------|
| RoHS                   | Free of hazardous substances according to RoHS 2011/65/EU                                                                    |
| Approvals and Listings | Meets ANSI/TIA/EIA-568A and 606, Tested in accordance with Telecordia GR-63-CORE, UL1863 - Communication Circuit Accessories |
| UL-Listed              | United States and Canadian safety standards                                                                                  |

### Environmental Conditions

|                              |                                     |
|------------------------------|-------------------------------------|
| Temperature Range, Operation | -40 °C to 70 °C (-40 °F to 158 °F ) |
|------------------------------|-------------------------------------|

### Design

|                                        |                                        |
|----------------------------------------|----------------------------------------|
| Lockable                               | Yes                                    |
| Number of Modules                      | 6                                      |
| Number of Panels/Cassettes per Housing | 6                                      |
| Housing Type                           | CCH                                    |
| Housing Color                          | Black                                  |
| Panel or Cassette Type                 | CCH                                    |
| Panel or Module Type                   | CCH                                    |
| Splice Tray Options                    | CCH Pigtailed Splice Cassette (CCH-CS) |
| Fiber Capacity                         | 144                                    |
| Lock Position                          | Front or rear                          |

# Closet Connector Housing (CCH) Three rack units, holds six CCH connector panels

CORNING

## Dimensions

|        |                     |
|--------|---------------------|
| Height | 135 mm (5.31 in)    |
| Width  | 496.5 mm (19.55 in) |
| Depth  | 433 mm (17.05 in)   |

## Ordering Information

|                    |                                                                                                                                              |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Product Number     | CCH-03U                                                                                                                                      |
| Height Unit        | 3 U                                                                                                                                          |
| Package Contents   | Closet Connector Housing 3U, 6 blank panels, Installation kit with mouting screws, Internal and external strain relief brackets, Label Cards |
| Shipping Weight    | 7.7 kg                                                                                                                                       |
| Shipping Height    | 257 mm (10.12 in)                                                                                                                            |
| Shipping Width     | 532 mm (20.94 in)                                                                                                                            |
| Shipping Depth     | 513 mm (20.2 in)                                                                                                                             |
| Units per Delivery | 1/1                                                                                                                                          |



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States  
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.