

CCHE Panel, SC Duplex 6 F, 50 µm multimode (OM3/4)

CORNING

Part Number: CCHE-CP06-E7

The panels are used with field-installable connectors or in applications where the preconnectorized cables are routed directly from the equipment to the piece of inter-connect hardware. This provides an efficient way to securely mate two or more connectors.

Closet connector housing panels are offered in 6-, 8-, 12-, 16- and 24-fibre panels for use with the LANscape® solutions hardware products. The panels are used with field-installable connectors or in applications where the pre-connectorized cables are routed directly from the equipment to the inter-connect hardware. The panels are available with a variety of industry-standard adapter types. In most applications, the closet connector housing panels are designed for applications where specified labeling and connector identification are required. This is accomplished by the use of colored icons with different symbols molded into the icon.

Features and Benefits


Designed to accommodate all industry-standard adapter types

Unique colour-coded connector labeling system

Universal approach is used

Available in 6-, 8- and 12-fibre count options in most adapter styles

Also available for copper modules 12-fibre ST Compatible Connector Panel, 12-fibre SC Duplex Panel, 24-fibre MT-RJ Connector Panel



CCHE Panel, SC Duplex 6 F, 50 µm multimode (OM3/4)

CORNING

Specifications

General Specifications

Fibre category	50 µm MM (OM3)
----------------	----------------

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Environmental Conditions

Temperature range, operation	-20 °C to 70 °C
------------------------------	-----------------

Design

Fibre count	6
Adapter colour front	Turquoise
Colour	Black
Number of adapters	3

Design - Adapter

Adapter housing colour	Turquoise
Adapter housing material	Composite
Keyed adapter	No
Shuttered adapter	No
Adapter type	SC duplex
Insert material	Ceramic

Dimensions

Width	35 mm
Weight	7000 kg

CCHE Panel, SC Duplex 6 F, 50 µm multimode (OM3/4)

CORNING

Ordering Information

Product Number	CCHE-CP06-E7
Shipping weight	32 kg
Shipping Height	250 mm
Shipping Width	190 mm
Shipping Depth	180 mm



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
00 800 2676 4641 • FAX: • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2026 Corning Optical Communications. All rights reserved.