

CCHE Panel, LC Duplex 12f, 50 µm multimode (OM3/OM4), shuttered

The Corning logo is displayed in white, uppercase letters on a solid blue rectangular background.

Part Number: CCHE-CP12-AD

The panels are used with field-installable connectors or in applications where the preconnectorized cables are routed directly from the equipment to the piece of inter-connect hardware. This provides an efficient way to securely mate two or more connectors.

Closet connector housing panels are offered in 6-, 8-, 12-, 16- and 24-fibre panels for use with the LANscape® solutions hardware products. The panels are used with field-installable connectors or in applications where the pre-connectorized cables are routed directly from the equipment to the inter-connect hardware. The panels are available with a variety of industry-standard adapter types. In most applications, the closet connector housing panels are designed for applications where specified labeling and connector identification are required. This is accomplished by the use of colored icons with different symbols molded into the icon.

Features and Benefits

Designed to accommodate all industry-standard adapter types

Unique colour-coded connector labeling system

Universal approach is used

Available in 6-, 8- and 12-fiber count options in most adapter styles

Also available for copper modules 12-fibre ST® Compatible Connector Panel, 12-fibre SC Duplex Panel, 24-fibre MT-RJ Connector Panel

CCHE Panel, LC Duplex 12f, 50 µm multimode (OM3/OM4), shuttered

CORNING

Specifications

General Specifications

Fiber Category	50 µm MM (OM3/OM4)
----------------	--------------------

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Environmental Conditions

Temperature Range, Operation	-20 °C to 70 °C
------------------------------	-----------------

Design

Fiber Count	12
Adapter Color Front	Aqua
Color	Black
Number of Adapters	6

Design - Adapter

Housing Color	Aqua
Housing Material	Composite
Keyed adapter	No
Shuttered adapter	Yes
Adapter Type	LC Duplex Shuttered
Insert	Ceramic

Dimensions

Width	35 mm
Weight	6 kg

CCHE Panel, LC Duplex 12f, 50 µm multimode (OM3/OM4), shuttered

CORNING

Ordering Information

Product Number	CCHE-CP12-AD
Shipping Weight	3 kg
Shipping Height	250 mm
Shipping Width	190 mm
Shipping Depth	180 mm



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
00 800 2676 4641 • FAX: • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2026 Corning Optical Communications. All rights reserved.